



Product Specification

Style Name	Crescent Rigid Plank
Construction	Class III High Performace LVP
Wear Layer Finish	Urethane w/ Double UV Coating
Wear Layer Thickness	12 mil
Overall Thickness	5mm (4mm SPC / 1mm EVA Pad)
Attached Cushion	1mm EVA Ethylene Vinyl Acetate

Features

Plank Edge	Square Edge
Texture	Standard Embossing
Plank Size	7" x 48"

Installation	Floating
--------------	-----------------

Testing

Impact Sound Conduction / ASTM E492-09	IIC 60
Sound Transmission Class /ASTM E90-09	STC 52
Slip Resistance / ASTM D2047	0.82 Dry / 0.78 Wet
Dimensional Stability / ASTM F2199	Pass
Residual Indentation / ASTM F1914	Pass
Static Load Limit / ASTM F970	Pass
Resistance to Heat / ASTM F1514	Pass
Resistance to Light / ASTM F1515	Pass
Resistance to Chemicals / ASTM F925	Pass
Radiant Flux / ASTM E648	>0.45 watts/cm2, NFPA Class I
Smoke Density / ASTM E662	Pass, <450

Warranty	10 Year Commercial
-----------------	---------------------------

Environmental

Indoor Air Quality	FloorScore Certified
--------------------	-----------------------------

