



## Product Specification

---

Style Name	<b>Heritage Mix</b>
Construction	<b>Class III High Performance LVP</b>
Wear Layer Finish	<b>Urethane w/ Double UV Coating</b>
Wear Layer Thickness	<b>20 mil</b>
Overall Thickness	<b>8mm (5mm WPC/1.5 IXPE/1.5mm Vinyl top)</b>
Attached Cushion	<b>1.5mm IXPE Cross Linked Polyethelene</b>

### Features

Plank Edge	<b>V Groove Painted Bevel</b>
Texture	<b>EIR (Embossed in Register)</b>
Plank Size	<b>Mixed Width 4.88"/6.85"/8.86"</b> <b>Mixed Length 19.45"/39.29"/59.05"</b>
Installation	<b>Floating</b>

### Testing

Impact Sound Conduction/ASTM E492-09	<b>IIC 62</b>
Sound Transmission Class/ ASTM E90-09	<b>STC 52</b>
Slip Resistance / ASTM D2047	<b>0.92 Dry/0.97 Wet</b>
Dimensional Stability / ASTM F2199	<b>Pass</b>
Residual Indentation / ASTM F1914	<b>Pass</b>
Static Load Limit / ASTM F970	<b>Pass</b>
Resistance to Heat / ASTM F1514	<b>Pass</b>
Resistance to Light / ASTM F1515	<b>Pass</b>
Resistance to Chemicals / ASTM F925	<b>Pass</b>
Radiant Flux / ASTM E648	<b>&gt;0.45 watts/cm2, NFPA Class I</b>
Smoke Density / ASTM E662	<b>Pass, &lt;450</b>

### Warranty

**15 Year Commercial**

### Environmental

Indoor Air Quality

**FloorScore Certified**