



Product Specification

Style Name	Conway Loose Lay
Construction	Fiberglass Reinforced Recycled PVC
Wear Layer Finish	Urethane w/ Double UV Coating
Wear Layer Thickness	20 mil
Overall Thickness	5mm
Attached Cushion	Non Skid Backing

Features

Plank Edge	Square Edge
Texture	Standard Embossing
Plank Size	6" x 48"

Installation	Loose Lay/Glue Down
--------------	----------------------------

Testing

Impact Sound Conduction / ASTM E492-09	IIC 47
Sound Transmission Class /ASTM E90-09	STC 53
Slip Resistance / ASTM D2047	0.84 Dry / 0.86 Wet
Dimensional Stability / ASTM F2199	Pass
Residual Indentation / ASTM F1914	Pass
Static Load Limit / ASTM F970	Pass
Resistance to Heat / ASTM F1514	Pass
Resistance to Light / ASTM F1515	Pass
Resistance to Chemicals / ASTM F925	Pass
Radiant Flux / ASTM E648	>0.45 watts/cm², NFPA Class I
Smoke Density / ASTM E662	Pass, <450

Warranty	15 Year Commercial
-----------------	---------------------------

Environmental

Indoor Air Quality	FloorScore Certified
--------------------	-----------------------------